



32ch DVR + DVD / Internet



32ch DVR with Remote Access & DVD Writer

High capacity 32 channel DVR for recording and managing a large amount of cctv cameras. Supplied with 1.5TB of storage enabling easy control of PTZ cameras and alarm inputs. Remote access to DVR for client side management with built in DVD Writer, USB and network backup.

Features

- 32ch video & 16ch audio input,
- up to 400fps recording with live monitor view
- MPEG4 Compression, Long Recording Time, Motion Detection
- Backup to DVD, USB or over Network / Internet
- Covert recording function
- Up to D1 resolution
- Rackmount design

Video	
Video input	32 channels
Loop output	32 channels
Input level	1.0V p-p \pm 10% Composite 75 \cdot unbalanced
Video standard	PAL
Display resolution	720*576
Display speed	Real time
Main TV output	1.0V p-p \pm 10% Composite 75 \cdot unbalanced
Camera name	Max 29 characters
Screen split control	4, 1+5, 3+4, 1+7, 3x3, 2+8, 1+12, 4x4, 2+17, 1+21, 5x5, 1+32, full screen, auto conversion, PIP
Screen rotate control	Continuousv
Image control	Contrast, brightness, hue
Audio	
Compression	ADPCM
Input channel	16 channels
Live output	1 channel
Recording	
Compression	Enhanced Mpeg 4
Resolution (pixels)	352x288 704x288 704x576
Maximum recording speed	400fps @ CIF, 200FPS @ HD1, 100FPS @ D1
Mode	Continuous / Scheduled / Motion detection / Sensor event / Quick instant / Intensive
Alarm frame setting	Pre alarm : 30 sec, Post: 180sec
Alarm duration	3-15 sec
Water marking	Supported (exported image only)
Searching	
Search method	Instant search / date / time / event / object / day search / real time / multi time
Date / time search	Selectable on map and calendar
Remote	
Monitoring environment	CMS, web CMS, CAMS (Innovative central automated & monitoring solution, option) Approx 9x clients accessible
Display	Display approx 36 screen full motion transmission / max 1400FPS real time transmission
Search	Search supporting multi client
Monitoring & recovery	
System logging	System logging (power failiure / video loss checkable etc.)
Monitoring	Two independent watchdog (Reliable HW watchdog + software watchdog) Automatic self diagnosis program built in (By interface with remote health checker)
Recovery	Auto reboot by watchdog
Alarm	
Sensor input	16 ports (NC / NO)
Alarm output	16 ports
Motion detection	Availiable for each camera, multiple detection level
Connector	
Video input	BNC 32
Audio input (mono)	RCA 16 ports
Main output	VGA
S-VIDEO (Main TV)	4 pin mini DIN
Sensor input	Terminal block (Include ground common 2)
Alarm output	Terminal block (Include ground isolated 2)
PTZ	RS-232, 422, 485 / Remote PTZ controller
Ethernet	RJ45, 10 / 100Mbps fast ethernet
USB 2.0	Front 2 ports, rear 4 ports
VGA Ouptut	15 pin female D-Sub

Backup

Archiving type	CDRW, DVDRW, USB, IEEE1394 external storage, IEEE1394 RAID1 External storage
Remote backup	Automatic scheduled backup support (3 DVR simultaneous backup)
Local backup	Instant backup / schedule backup (DVR file format with backup viewer)
Backup viewer	Autorun playback support with viewer
Electrical	Power source: 115~240V AC (47~63 Hz) / power consumption : Approx 380 Watt
Environment	Operating temp: +5 ~ +40°C / Storage temp: -5 ~+60°C / Humidity 30-80%RH (Non-condensing)
Physical	Colour: Black 4U / Dimension 500W * 190H * 450D Weight: ~22kg

[download](#) | [print](#) | [support](#) | [buy](#)

*Specifications are subject to change without notice.

Copyright © 2008, Securicorp Ltd. All rights reserved. [32ch DVR](#)