


2.0 Megapixel WDR, Starlight, AF, IR Bullet Network Camera

Key Features

- Starlight Illumination
- 4X Optical Zoom & Auto Focus
- Up to 120 dB WDR (Wide Dynamic Range)
- Smart IR, up to up to 100m (328 ft) IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- Day/Night Functionality
- H.265
- Triple Streams
- ROI (Region of Interest)
- 9:16 Corridor Mode
- Customized OSD
- ONVIF Conformance
- Support PoE Power Supply, IP67
- Wide Temperature Range: -40°C to 60°C (-40°F to 140°F)
- Wide Voltage Range of ±25%



Dimensions



Technical Specification

Model	SCL-OBL02MVIR-SL26UD04X
Product Name	2.0 Megapixel WDR, Starlight, AF, IR Bullet Network Camera
Camera	
Sensor	1/2.8", 2.0 Megapixel, Progressive Scan CMOS
Shutter	Auto/Manual, 1/6~1/8000s
Lens	2.8~12mm@F1.6; DC-Iris
Angle of View (H)	97° (wide)~ 35° (tele)
Zoom/Focus	4X Optical Zoom / Auto Focus
Min. Illumination	Colour: 0.002 Lux (F1.6, AGC ON) 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
WDR	120dB
IR	Smart-IR, up to 100m (328ft) IR range

Video	
Max. Resolution	1920 × 1080
Video Compression	H.265, H.264, MJPEG
Frame Rate	1080P (1920*1080): Max. 30 fps
9:16 Corridor Mode	Supported
ROI	Supported
Video Streaming Available	Triple
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
Audio	
Audio Compression	G.711
Two-way audio	Supported
Storage	
Edge Storage	Micro SD, Up to 128 GB
Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, SIP, QoS
Compatible Integration	ONVIF, API
Interface	
Audio I/O	Audio cable 1 Input: impedance 35 kΩ; amplitude 2 V [p-p] 1 Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	2 / 1
Network	10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
Serial	1 RS485
General	
Power	DC12V ± 25%, AC24V ± 25% or PoE (IEEE802.3 at) Power consumption: 13.7W
Material	Cast aluminum
Dimensions (L × W × H)	305.5 × 104.1 × 97.3mm (12.0" × 4.1" × 3.8")
Weight	1.65 kg (3.6 lb)
Working Environment	-40° C ~ +60° C (-40° F ~ 140° F), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP67