


2.0 Megapixel, WDR, Motorized Varifocal, Water-Proof, IR Bullet Network Camera

Key Features

- ❖ Day/Night Functionality
- ❖ Smart IR, up to 30m (98 ft) IR distance
- ❖ Up to 120 dB Optical WDR (Wide Dynamic Range)
- ❖ 3D DNR (Digital Noise Reduction)
- ❖ H.265
- ❖ Triple Streams
- ❖ ROI (Region of Interest)
- ❖ 9:16 Corridor Mode
- ❖ Customized OSD
- ❖ ONVIF Conformance
- ❖ Support PoE Power Supply
- ❖ Wide Temperature Range: -35°C to 60°C (-31°F to 140°F)
- ❖ Wide Voltage Range of ±25%
- ❖ IK10 Vandal Resistant
- ❖ IP66



Dimensions



Technical Specification

Model	SCL-OBL02MVIR-WD22PDZ
Product Name	2.0 Megapixel, WDR, Motorized Varifocal, Water-Proof, IR Bullet Network Camera
Camera	
Sensor	1/3", 2.0 Megapixel, Progressive Scan CMOS
Shutter	Auto/Manual, 1/6~1/8000s
Lens	2.8~12mm @F1.4 ; Angle of view: 90° ~ 28°
Zoom/Focus	Motor Drive
Min. Illumination	Colour: 0.02 Lux (F1.4, AGC ON) 0 Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 30m (98 ft) IR range
S/N	>52 dB
WDR	Optical WDR (up to 120 dB)

Video	
Max. Resolution	1920 × 1080
Video Compression	H.265, H.264, MJPEG
Frame Rate	1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps
9:16 Corridor Mode	Supported
ROI	Supported
Video Streaming Available	Triple
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
Audio	
Audio Compression	G.711
Two-way audio	Supported
Storage	
Edge Storage	Micro SD, up to 128 GB
Network	
Protocols	L2TP, Ipv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, Qos, NTP, FTP, HTTP, SNMP, SIP
Security	User Access Log, Password Protection, HTTPS Encryption, RTSP Authentication, ARP Binding, IP Address Filtering, Video Watermark, IEEE 802.1x
Compatible Integration	ONVIF, API
Interface	
Audio I/O	Audio Cable Input: impedance 35 kΩ; amplitude 2 V [p-p] Output: impedance 600 Ω; amplitude 2 V [p-p]
Alarm I/O	1 / 1
Network	10M/100M Base-TX Ethernet
General	
Power	12 V DC, or PoE (IEEE802.3 af) Power consumption: Max 9W
Material	Cast aluminum
Dimensions (L × W × H)	253.4 × 86 × 71.7 mm (9.98" × 3.4" × 2.8")
Weight	0.58kg (1.28lb)
Working Environment	-35 °C ~ +60 °C (-31 °F ~ 140 °F), Humidity ≤ 95% RH(non-condensing)
Vandal Resistant	IK10
Ingress Protection	IP66