

Key Features

- ❖ H.264 Video compression, AVI, dual-stream support.
- ❖ Supports 1-25 frames per second adjustable; 25 FPS below 2.0 Megapixel.
- ❖ High performance 2 megapixel 1/3" SONY Sensor.
- ❖ 1920(H)×1080(V) Image Resolution.
- ❖ ICR(Intelligent character recognition) optical filter switch functions.
- ❖ IP 66,vandalproof, Bullet.
- ❖ Features Pan-tilt control support, local recording & record history.
- ❖ Network protocol:RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF & more.



Technical Specification

| | |
|----------------------------|--|
| Model | SCP-FBX020POE-69Q |
| Product Name | 2.0 Megapixel HD Box Network Camera |
| Specification | 1080P HD Camera |
| Sensor | 2 Megapixel 1/3" SONY Sensor |
| Image Resolution | 1920(H) × 1080(V) |
| Video Code | H.264 video Code, Dual-Stream, AVI support. |
| Video Compression Bit Rate | 25fps under 2.0 Megapixel, Supports 1-25 frames/second adjustable |
| Dual Stream | Main Stream:1920 × 1080, 1280 × 720:Sub streams:640 × 360, 480 × 270, 52 × 288, 320 × 240, 352 × 192, 320 × 192, 288 × 192, 256 × 192; |
| Minimum Illumination | Colour :0.1Lux@F1.1, black and white 0.01 Lux@F1.1 |
| AGC | Auto |
| White Balance | Auto |
| Network Protocol | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF |
| Security | User Access Log, Password Protection, HTTPS Encryption, RTSP Authentication, IEEE 802.1x |
| Data Storage | Videotype storage, screenshot picture storage |
| Storage Method | Manual, Auto |
| Analog Output | One analog video output;support CVBS Standard, PAL/NTSC optional |
| Optional Function | PoE |
| Operating Temperature | -10°C - +55°C |
| Power Supply | DC12V ± 10% |
| Power Consumption | 180mA/420mA |
| Lens | C/CS interface |
| Weight | 0.60KG |
| Size | 158*75*55mm |

Securicorp Systems UK Ltd, All Rights Reserved. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to product. Securicorp Systems UK Ltd may make changes to specifications and descriptions without notice.